



*P.O. Box 2834
Poulsbo, WA 98370
Tel. 360-697-8629
Fax 360-697-5425*

Levelok Permanent Mount Ladder Leveling System: Specifications

Standards Compliance - Meets all ANSI and OSHA requirements for Portable Ladders and / or Ladder Accessories, up to Type 1AA, 375 pound duty rating.

Ladder Compatibility - Fits most aluminum, fiberglass and wood, extension, combination, articulating and sectional ladders.

Installation Method - Attaches to ladder rail with 3, 5/16" diameter, pre-installed, mounting bolts, fender washers and nylon locking nuts. Drill template included in retail kits.

Bolt Spacing – 4-1/2" on center

Leveler Outer and Inner Leg – Aircraft Aluminum; Anodized

Locking System - Stainless steel, double-row ratcheting system, adjusts up to 10" in 3/16" increments.

Safety Lock – Fully Automatic, Stainless steel, Back-up Safety Lock. Automatically deploys when weight is placed on the ladder / leveler / shoe assembly.

Weight of Ladder Leveler - 4 pounds, 13 oz.

Dimensions: Leveler in Fully Retracted Position - 19.5" x 3.25" x 2.25"

Dimensions: Leveler in Fully Extended Position - 29.5" x 3.25" x 2.25"

Warranty – 2 years; Parts and labor for manufacturing defects.

Packaging options:

1.) Retail Leveler Kit: Model LL-STB-1AL, SL: 2 Ladder Levelers, Template, Hardware kit (for installation on ladders, up to and including a Type 1AA) Instruction manual. Retail, mailer carton. AL=Standard bolt length. SL=Long Bolt Length.

2.) Levelers in Bulk Pkg: Model LL-STB-1Bulk, XLB: 2 Ladder Levelers with washers and locknuts only. Bulk packaged. 1Bulk=Standard Bolt Length. XLB=Extra Long Bolt Length.